

1. THE COVERS ARE RECESSED TO ACCEPT A SCREED WITH A TILE OR RESIN FLOOR FINISH.
2. INSTALLED, THEY GIVE AN AESTHETIC APPEARANCE LEAVING ONLY THE POLISHED PERIMETER EDGE BAR VISIBLE, LOCKABLE AND DOUBLE SEALED.
3. COVERS ARE REMOVED FOR ACCESS BY REPLACING THE HOLDING DOWN BOLTS WITH THE THREADED LIFTING HANDLES SUPPLIED.
4. THE 4200 COVERS ARE SUPPLIED AS INDIVIDUAL OR MULTIPLE UNITS.
5. MULTIPLE COVERS CAN BE USED IN CONJUNCTION WITH A STAINLESS STEEL CHANNEL TO FORM A CONTINUOUS DUCT.
6. LOADING CAPACITIES ARE PEDESTRIAN, SPECIALLY DESIGNED HEAVY-DUTY COVERS ARE AVAILABLE ON REQUEST.
7. AVAILABLE IN GRADE 304 OR 316 STAINLESS STEEL.

STAINLESS STEEL - GRADE 304 (BS 1449:PART 2:1983) 1.4301 (BS EN 10088-1:1995)
STAINLESS STEEL - GRADE 316 (BS 1449:PART 2:1983) 1.4436 (BS EN 10088-1:1995) - ALTERNATIVE OPTION

1. CAREFULLY UNLOAD THE ASSEMBLED COVER AND REMOVE PACKAGING MATERIAL.
2. FIT THE OUTER FRAME OVER THE MANHOLE AND ADJUST TO FINISHED FLOOR LEVEL.
3. FIX AND BED-IN THE OUTER FRAME.
4. LOCATE THE RECESSED COVER IN THE FRAME, SECURING IN POSITION WITH SUPPLIED FIXINGS.
5. FILL WITH SUITABLE INFILL LEAVING ADEQUATE RECESS FOR FLOOR FINISH, BUT ENSURING NO CAVITIES ARE PRESENT WHICH WILL AFFECT THE STRUCTURAL INTEGRITY OF THE COVER.
6. FINALLY, APPLY FLOOR FINISH.

E-MAIL: Info@componentdevelopments.com
WEBSITE: www.componentdevelopments.com

PLEASE CONTACT US DIRECTLY FOR ALL REPLACEMENT PARTS. FULL TECHNICAL ASSISTANCE CAN BE PROVIDED.

